



Part No.	V-LCD8P-02
<b>Size</b>	7.9" Diagonal
<b>Active Area</b>	6.35"H x 4.64"W
<b>Input Signal</b>	NTSC/PAL Auto
<b>Format</b>	1440 x 468 Pixels
<b>Pixel Config.</b>	Stripe
<b>Dimensions</b>	6.79"W x 5.20"H x 0.27"D
<b>Color</b>	Full Color
<b>Back Light</b>	Built-in
<b>Controls</b>	Color, Brightness, Contrast, Tint via OSD
<b>Supply Voltage</b>	12VDC, 1.0A

To operate unit, supply 12VDC @600mA of power (Marshall V-PS12-1000, not included) into the red coaxial power jack. Supply an NTSC or PAL composite video signal to the yellow RCA connector. The panel comes with two boards that have buttons mounted on them. The board with the single button is the ON/OFF switch. The other button board has three buttons, the first button is MENU/SELECT and the second and third buttons are UP and DOWN, respectively. The panel automatically detects if the signal is NTSC or PAL. To adjust the picture, press the MENU/SELECT button and use the on-screen display to access contrast, color, and tint. To adjust the brightness, press the UP and DOWN buttons without being in the on-screen menu. For mounting dimensions see above.